



# LED T5 Direct Replacement



## Move forward. All new T5.



**SHATTER RESISTANT**



### FEATURES

**25.5W 3300lm 4ft LED T5 Frost**  
**High Lumens Efficacy**  
**DLC 4.2, UL, cUL listed**

- Dimmable (ballast dependent)
- 50,000 hour life
- Ballast compatible direct replacement for T5 fluorescent
- Shatter Resistant - NSF/ANSI 2 coating also meets standards for splash zones of food equipment
- Easy installation Plug & Play
- No flicker, mercury free, instant on
- 5-year warranty

### APPLICATION


- Offices
- Schools
- Hospitality
- Retail
- Restaurant
- Shopping Malls

### ADDITIONAL INFO

- Fits into existing fixtures
- Compatible with Programmed/ Rapid/ Instant Start Ballast<sup>2</sup>
- Operating Temperature -20°C ~+45°C

<sup>2</sup>Refer to our compatibility list.

### DIAGRAM



ORDER CODE	DESCRIPTION	BALLAST COMPATIBLE	LAMP POWER	VOLT	BASE	LUMENS	CCT(K)	LIFE HRS	BEAM ANGLE	CRI	PF	MOL (IN)	CASE QTY.
L2214-4431	ILLX T5DR 25.5W 40K 4FT 3250LM Frost	✓	25.5W	120-277,347V	G5	3250	4000K	50,000	160°	80+	0.9	48	25
L2214-4531	ILLX T5DR 25.5W 40K 4FT 3300LM Frost	✓	25.5W	120-277,347V	G5	3300	5000K	50,000	160°	80+	0.9	48	25

Available in other wattages, color temperatures and sizes (MOQ).

Distributed by



**Toronto | Calgary | Halifax**

Tel: 1-905-264-1125 Toll Free: 1-800-361-7820 Fax: 1-905-264-1175  
 Email: [information@interadwes.com](mailto:information@interadwes.com) | Website: [www.interadwes.com](http://www.interadwes.com)  
 Head Office: 1-180 New Huntington Road, Vaughan, ON L4H 0P5

NOTE: Preliminary specifications. Subject to change without notice.