



LED T8 Direct Replacement

Move forward. All new T8.



SHATTER RESISTANT

FEATURES

13W 2000lm, 15W 2200lm 4ft LED T8 Frost High Lumens Efficacy DLC 4.2, UL, cUL listed

- Dimmable (ballast dependent)
- 50,000 hour life
- Ballast compatible direct replacement for T8 fluorescent
- Shatter Resistant - NSF/ANSI 2 coating also meets standards for splash zones of food equipment
- Easy installation Plug & Play
- No flicker, mercury free, instant on
- 5-year warranty

APPLICATION


- Offices
- Schools
- Hospitality
- Retail
- Restaurant
- Shopping Malls

ADDITIONAL INFO

- Can be used with shunted or non-shunted sockets
 - Fits into existing fixtures
 - Compatible with Programmed/ Rapid/ Instant Start Ballast²
 - Operating Temperature -20°C ~+45°C
- ²Refer to our compatibility list.



DIAGRAM



ORDER CODE	DESCRIPTION	BALLAST COMP.	LAMP POWER	SYSTEM POWER	VOLT	BASE	LUMENS	CCT(K)	LIFE HRS	BEAM ANGLE	CRI	PF	MOL (IN)	CASE QTY.
L2314-1431	ILLX T8DR 13W 40K 4FT 1900LM Frost	✓	13W	16W	120-277,347V	G13	1900	4000K	50,000	160°	80+	0.9	48	25
L2314-1531	ILLX T8DR 13W 50K 4FT 2000LM Frost	✓	13W	16W	120-277,347V	G13	2000	5000K	50,000	160°	80+	0.9	48	25
L2314-2431	ILLX T8DR 15W 40K 4FT 2100LM Frost	✓	15W	18W	120-277,347V	G13	2100	4000K	50,000	160°	80+	0.9	48	25
L2314-2531	ILLX T8DR 15W 50K 4FT 2200LM Frost	✓	15W	18W	120-277,347V	G13	2200	5000K	50,000	160°	80+	0.9	48	25

System Power is the total power consumption that LED tube is working with ballast. It varies with different ballast factor. Available in other sizes and wattages, color temperatures and sizes (MOQ).

Distributed by



Toronto | Calgary | Halifax
 Tel: 1-905-264-1125 Toll Free: 1-800-361-7820 Fax: 1-905-264-1175
 Email: information@interadwes.com | Website: www.interadwes.com
 Head Office: 1-180 New Huntington Road, Vaughan, ON L4H 0P5