



LED T8 Direct Replacement

Move forward. All new T8.



SHATTER RESISTANT

FEATURES

13W 2000lm, 15W 2200lm 4ft LED T8 Frost
High Lumens Efficacy
DLC 4.2, UL, cUL listed

- Dimmable (ballast dependent)
- 50,000 hour life
- Ballast compatible direct replacement for T8 fluorescent
- Shatter Resistant - NSF/ANSI 2 coating also meets standards for splash zones of food equipment
- Easy installation Plug & Play
- No flicker, mercury free, instant on
- 5-year warranty

APPLICATION


- Offices
- Schools
- Hospitality
- Retail
- Restaurant
- Shopping Malls

ADDITIONAL INFO

- Can be used with shunted or non-shunted sockets
 - Fits into existing fixtures
 - Compatible with Programmed/ Rapid/ Instant Start Ballast²
 - Operating Temperature -20°C ~+45°C
- ²Refer to our compatibility list.



DIAGRAM



ORDER CODE	DESCRIPTION	BALLAST COMPATIBLE	LAMP POWER	VOLT	BASE	LUMENS	CCT(K)	LIFE HRS	BEAM ANGLE	CRI	PF	MOL (IN)	CASE QTY.
L2314-1431	ILLX T8DR 13W 40K 4FT 1900LM Frost	✓	13W	120-277,347V	G13	1900	4000K	50,000	160°	80+	0.9	48	25
L2314-1531	ILLX T8DR 13W 50K 4FT 2000LM Frost	✓	13W	120-277,347V	G13	2000	5000K	50,000	160°	80+	0.9	48	25
L2314-2431	ILLX T8DR 15W 40K 4FT 2100LM Frost	✓	15W	120-277,347V	G13	2100	4000K	50,000	160°	80+	0.9	48	25
L2314-2531	ILLX T8DR 15W 50K 4FT 2200LM Frost	✓	15W	120-277,347V	G13	2200	5000K	50,000	160°	80+	0.9	48	25

Available in other wattages, color temperatures and sizes (MOQ).

Distributed by



Toronto | Calgary | Halifax

Tel: 1-905-264-1125 Toll Free: 1-800-361-7820 Fax: 1-905-264-1175
 Email: information@interadwes.com | Website: www.interadwes.com
 Head Office: 1-180 New Huntington Road, Vaughan, ON L4H 0P5